

PROXIMA PLUS

All you need is a key



Zetor

These tractors are from the mid-size performance category focusing on their simple service, long life expectancy, versatility, and their low cost.

Engine

Proxima Plus tractors are powered by their own range of Zetor engines, which fulfill the Tier III emission standards and at the same time feature their low operational costs as well as high reliability. These engines are constructed with a viscous exhaust coupling that contributes to their cost-effective operation and noise level reduction.

Engine Bonnet

The tractors have a new engine bonnet design that opens upwards in a tilting fashion. This maneuver allows for an easier accessibility of the tractor engines for easy servicing and maintenance. Along with these features, the new engine bonnet brings new lighting and a higher number of headlamps as part of the standard design as well as part of the optional features.

Cabin

The cabin has all of the main controls ergonomically placed with an analogue display that is easily legible.

New elements of the cabin are:

- 150 L fuel tank capacity
- New creepers

Tractor Chassis

- Rated tractor speed: 40 Km/h (30 Km/h optional) for all model ranges
- New tire dimensions: 540/65R34, 520/70R34, and 600/65R34 (commencing in 2008)



[TRACTOR IS ZETOR]

ZETOR PROXIMA PLUS SPECIFICATIONS

Since 1946
TRACTOR IS ZETOR

All you need is a key

MODEL	UNITS	Z 8541	Z 9541	Z 10541
ENGINE				
Model		Zetor 1205	Zetor 1005	Zetor 1305
Power ECE R24	kW/HP	60/82	66/90	74/100
Rated speed	rpm		2200	
No. of cylinders			4	
Aspiration			turbocharged	
Bore/Stroke	mm		105/120	
Displacement	cc		4156	
Torque reserve	%		35	
Emissions			TIER III	
CLUTCH				
Type			dry, single plate, hydraulic control	
Diameter	mm		310	
Lining			cerametallic	
TRANSMISSION				
Type			two-stage power shift, mechanical	
Shifting			fully synchronised	
Gears forward/reverse			16/16	
Speed	kmph	30 and 40		40
PTO SHAFT				
Type			live/ground speed, wet multi-plate PTO clutch	
Speeds	rpm		540/1000 (540/540E)	
Front PTO - speed			+1000 (-1000)	
HYDRAULICS				
Type			mechanical, top link draft sensing	
Three point linkage			category I and II	
Control			position, draft, mixed	
Lift capacity	kN		41.5	
Operating pressure	MPa		18	
Pump capacity	(l/min)		50	
SCV's			three set of remotes standard	
OTHER				
Drive system			4WD	
Operator's station			cab version	
Steering			hydrostatic	
Service brake			wet disc brake, hydraulic control	
Parking brake			mechanical control	
Front axle 4WD			Carraro 20.16, wet brakes in wheels	
Rear axle			differential lock engaged electro-pneumatically	
DIMENSIONS				
Maximum length	mm		4324	
Maximum width	mm		1910	
Maximum height	mm		2692	
Wheel base	mm		2328	
Ground clearance	mm		402	
Standard front tyres			11.2-24	
Standard rear tyres			16.9-30	
Weight	kg		4010	

adjustable steering wheel ■ A/C ■ adjustable trailer hitch ■ pick-up hitch ■ front three point hitch ■ front and rear weights
block heater ■ mate's seat ■ hydraulic or air pressure trailer brakes ■ choice of tyre combinations



Zetor

Info:

www.zetor.com

PROXIMA PLUS